

ARMY RESEARCH LABORATORY



COMBIC Modifications to Determine Aerosol Cloud Densities for Multiple Obscurant Input Sources

Michael Mungiole and Alan Wetmore

ARL-TR-865

March 2001

Approved for public release; distribution unlimited.

20010410 155

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

Citation of manufacturer's or trade names does not constitute an official endorsement or approval of the use thereof.

Destroy this report when it is no longer needed. Do not return it to the originator.

Army Research Laboratory

Adelphi, MD 20783-1197

ARL-TR-865

March 2001

COMBIC Modifications to Determine Aerosol Cloud Densities for Multiple Obscurant Input Sources

Michael Mungiole and Alan Wetmore

Computational and Information Sciences Directorate

Approved for public release; distribution unlimited.

Abstract

Modifications were made to the Combined Obscuration Model for Battlefield Induced Contaminants (COMBIC) code to obtain aerosol cloud-density values for multiple obscurant types. The main purpose of COMBIC has traditionally been to obtain the transmittance or optical depth for one or more lines of sight (LOSs). If one specifies optical depth, uses consistent units, and ensures that the product of mass extinction coefficient and optical path length is unity, output values will be numerically equal to the cloud density (g/m^3). This report provides information on the required input values, the modifications made to COMBIC, and the resulting output obtained when one or more sources comprising various obscurant types are provided as input. Examples are included that show various cases containing sources with one or more obscurant types as input. The density output files and the resulting visualized clouds are also given in this report. Specific recommendations for the appropriate input values required to produce valid cloud-density grids are indicated.

Contents

1	Introduction	1
2	Theory and Methods	2
3	Code Description and Modifications	4
4	Results	7
5	Conclusions	11
	References	12
	Appendices	13
A	Header Variables	13
B	Sample Inputs and Output	15
B-1	Input File for Five Sources, Each of a Different Obscurant Type	15
B-2	Abbreviated Density Output File for Five Sources, Each of a Different Obscurant Type	17
B-3	Input File for Two Sources of the Same Obscurant Type . . .	19
	Distribution	21
	Report Documentation Page	27

Figures

1	Vis5D visualization of five clouds, each of a different obscurant type	9
2	Vis5D visualization of five clouds for case with lower spatial resolution	9
3	Vis5D visualization of two clouds of same obscurant type	9

1. Introduction

The Combined Obscuration Model for Battlefield Induced Contaminants (COMBIC) [1] has been used primarily by researchers to determine aerosol cloud sizes and positions and the reduction in the transmittance of electromagnetic energy for signals passing through these clouds. COMBIC data structures are optimized for calculating path integrals rather than providing cloud descriptions. The standard version of the COMBIC software allows the user to specify the location of one or more observers and targets to determine the transmittance along observer-to-target lines of sight (LOSs). It first computes time-dependent cloud skeletons and optical property descriptions for aerosols, which include explosions, munitions, dust, debris, and smoke. The scenarios for which COMBIC has been designed may be large, in that tens to hundreds of different obscuration sources and observer-to-target LOSs are considered simultaneously.

A particular feature of COMBIC is its ability to calculate either transmittance or optical depth. When the user selects the optical depth option, the process for obtaining density values is fairly straightforward. If one uses the appropriate units for relevant variables (mass extinction coefficient and optical path length) and the product of mass extinction coefficient and optical path length has the value of unity, then the optical depth is equal in magnitude to the aerosol cloud density. Hence, one can select appropriate input values to determine the density at desired locations and times.

Recently, we modified COMBIC to develop three-dimensional density fields in which aerosol cloud densities are printed at specified locations and time values. We did this because of a need to have smoke cloud densities processed as part of the Weather and Atmospheric Visualization Effects for Simulation (WAVES) package [2]. This package, which handles multiple clouds, predicts illumination and radiance information for a three-dimensional variable atmosphere. The modifications described in this report will help in allowing one to consider spatial and temporal variability of multiple smoke clouds. Also, the structure of these smoke clouds can be compared to the coarser structure of the clouds currently exhibited in WAVES. Appropriate header information that describes the relevant output, along with its size, is also included with the density output. In most of the work to date, we have been using three-dimensional grids on the order of magnitude of 0.1 to 0.5 km in each direction.

2. Theory and Methods

Transmittance is the quantity representing the fraction of electromagnetic energy that remains in the beam after passing along the optical path. In COMBIC, transmittance is calculated from the "Beer-Lambert" law,

$$T = e^{-\alpha CL}, \quad (1)$$

where α is the mass extinction coefficient and CL is the integral of the aerosol concentration (C) over the optical path length (L). The product αCL is dimensionless and is referred to as the optical depth. If the product of the mass extinction coefficient, α , and the optical path length, L , is unity, it is evident that the optical depth and the concentration (or density) are equal in magnitude. The units typically used are as follows: α , m^2/g ; C , g/m^3 ; and L , m .

This modified version of COMBIC uses this feature to determine density values for each individual volumetric cell at each point in time. The modifications to the coding were primarily made in subroutines CNTUR and BTRANS. Originally, CNTUR was used to produce a printer plot file, which was a gray-scale plot of transmission or optical depth. Modifications were made to obtain the actual aerosol cloud-density values that were printed to the density file named in standard input. Prior to printing the density data, we printed several header values to ensure compatibility with the Vis5D software [3] used to visualize the density data.

COMBIC allows the computations to be performed in two phases. The first phase produces a cloud history file that contains the data for each cloud and includes all meteorological influences except wind direction. Each obscurant type is indicated on a separate MUNT card within phase I. In the second phase, COMBIC builds a user-defined scenario of smoke and dust sources. The path-integrated concentration is determined for each observer-target pair and the transmittance is then calculated at each of seven wavelength bands (ranging from visible to far IR wavelengths) in the original version. In determining the printer plot, one needs to note that there would normally be only a single SLOC card as part of the phase II input that would indicate which obscurant type is to be produced. Changes were made to the COMBIC code, however, that made the inclusion of more than one obscurant type meaningful. The transmittance for each obscurant type was printed in standard output for the wavelength band of 0.4 to 0.7 μm ; this supplants the printing of transmittance at each of the seven wavelength bands. Also, the aerosol cloud densities at each specified location, instant in time, and obscurant type are printed to a density output file to be used for further analysis or visualization.

The individual density values for each obscurant type were obtained by creating an array variable (CLTOT) that was used in subroutine BTRANS to store the density value for each obscurant type. Within BTRANS, separate subroutines are called in different sections of the code to calculate the densities for puffs and plumes. The densities for these different clouds are then combined within BTRANS for each obscurant type to obtain the total density at each location and time.

The COMBIC code allows the cloud formed to propagate below ground. While this may be useful for selected cases, the modifications were made with the intention of determining densities above ground level. Hence, a value of $Z = 0$ was considered as the minimum Z -value for the observer-to-target LOS. This factor, in combination with the selection of the Z -component of the observer and target locations (on the OLOC and TLOC cards, respectively) indicates the smallest Z -value for which the density is determined. As an example, if the cells were to be represented by cubes 0.5 m on a side, then the Z -value for the observer and target would be 0.5 and 0.0, respectively, and the smallest Z -value for which the density is determined would be at 0.25 m.

3. Code Description and Modifications

To allow COMBIC to provide densities as an output of the model, we had to make several modifications to the code. The file in which the density values are output is specified in standard input. Hence, in addition to the FILE card for the direct access cloud-history file (unit 9), another FILE card is needed for the aerosol cloud-density file (unit 12). This file gives the density values, formatted to one value per line. The header values are output before the densities are written to the file. Included in these header values are the variables that determine the size of the density file, namely, the number of obscurant types, time steps, and cells in the horizontal (X), depth (Y), and vertical (Z) directions. A complete list of the header variables that precede the density data is given in appendix A.

In the earlier version, a two-dimensional printer plot was produced if there was a VIEW card detected in the phase II input. This occurred whether one selected transmission or optical depth. As was originally the case for COMBIC, the VIEW card provides the size of the grid in the X - and Y -directions (variables CLOSW and VLOSW, respectively) and the number of cells (CLOSD and VLOSD) in these respective directions. Now, the input requirements include providing grid information for the vertical direction also, and the previously unused last two positions on the TPOS card are used to input size (ZLOSW) and number of cells (ZLOSD) for this direction. Except for these last two values on the TPOS card, one should set all other values to 0.0. The GREY card is needed for a single variable only, CLOPT, which must be set to 1.0 to ensure that optical depth, not transmittance, is the desired output.

Some cautionary words are necessary regarding the X -, Y -, and Z -values selected for observer and target locations. Since the modifications leading up to this version were made such that densities are calculated for a series of X - Y planes, the LOS is parallel to the Z -axis, a measure of the height above the surface. Hence, the observer and target must have the same value for both the X - and Y -coordinates. For appropriate sign convention, the Z -coordinate of the observer (ZOBS) should be larger than that of the target (ZTAR). In addition, the LOS should be centered within the cell along the Z -direction to ensure that each density is calculated at the center of the cell. Also, since Z is incremented, one must select ZOBS and ZTAR centered on the lowermost cell, i.e., closest to the surface. As an example, if one wants to obtain densities as close to the ground as possible and there are five cells in the Z -direction with the length (size) of 15 m in the Z -direction, then the lowest cell is between 0 and 3 m and centered at 1.5 m. One should select ZOBS = 2.0 and ZTAR = 1.0 to get an LOS path length of 1 m. (The 1-m length corresponds to an assumption that the altered mass extinction coefficient is $1 \text{ m}^2/\text{g}$.) The X - and Y -coordinates on the OLOC (and TLOC)

cards represent the center of the X - Y plane of the grid. The densities are calculated at the center of each three-dimensional cell.

The size of the Y -dimension (VLOSW) on the VIEW card is called the vertical extent of viewport. The word vertical was used because it represented the vertical coordinate in the two-dimensional printer plots that were output in the original version of COMBIC. For the three-dimensional case presented in this report, the Y -dimension actually represents the width or depth while the Z -dimension is called the height or vertical position.

The maximum number of allowable sources (INOT) was dimensioned to 50. This is probably a much larger value than is needed and was selected because of the possibility of more than one source having the same obscurant type, which has values from 1 through 30. Because of this possibility, coding was added to SDREAD to eliminate duplicate density-array values for different sources having the same obscurant type. The algorithm initially sets the number of obscurant types (NUMOT) equal to the number of sources and decrements NUMOT each time a duplicate obscurant type is read from input while moving remaining obscurant type values into the next lower array value. The final value calculated for NUMOT represents the number of unique obscurant types that are input for the simulation. INOT and NUMOT were placed in common block CON.

The transmission output printed at the end of the phase II portion of the standard input was modified because we are using only a single wavelength band (0.4 to 0.7 μm). Originally the transmittance at each wavelength band and the optical depth were printed, but now each obscurant type has a different optical depth. Hence, we modified it so that it now prints at each step the transmittance for this band through the observer-to-target LOS and the corresponding optical depths for a maximum of 10 different obscurant types. This number was selected because of the convenience of the data format (i.e., the data for each time step are on a single line of output). If more than 10 obscurant types were used in a simulation, the coding would need to be modified to print the obscurant type values in an appropriate format.

Modifications in BTRANS included determining cumulative values for CLTOT for each obscurant type by making CLTOT an array variable. If a particular source produces both a plume and a puff, the plume portion of the code is executed first. Because of this, the CLTOT value from the plume section of the code was added to the CLTOT calculation in the puff portion to determine the overall density for each time and cell location. CLTOT is then passed to CNTUR, which prints out the density values. Previously, the value of the ODTOT variable in BTRANS was passed to CNTUR and this value was used to plot the transmittance or optical depth. Since only a single wavelength band is printed as output, all loops for the seven wavelength bands were dropped from the coding within BTRANS.

The variable CONC in subroutine CNTUR is used to hold the density values printed to the output file. CONC is a five-dimensional array; these are the number of time steps, the number of different obscurants, and the

number of cells in each of the three orthogonal directions. The array representing the number of obscurants was dimensioned to 30, which is also the number of different obscurant types available in the model. The time step array was dimensioned to 20 because this is currently the maximum number of time steps that can be accommodated by Vis5D. If one desires to visualize the data for more than 20 time steps, the appropriate Vis5D program can easily be modified and recompiled. The number of cells in the three orthogonal directions were each dimensioned to 50.

To help reduce the size of the density file, one must ensure that the first time step for which density values are printed is the first time step where an aerosol cloud for any source appears in the simulation. Density values are then printed until the specified time (the TEND variable on the LIST card) is reached. If all density values are zero for the selected obscurant types, time steps, and cell values, a message is printed to the density file indicating that no aerosol clouds appeared for the time and volume selected. Also, no data are sent to the density file when all values are zero.

For the original version of COMBIC, one needed to indicate the correct value of CLTYP, which is the value of the obscurant type on the EXTC card. This is no longer necessary and would be irrelevant since there would usually be more than one obscurant type value for the multiple obscurant version used to calculate densities. The input value selected for CLTYP, however, will affect the calculated transmittance. The remaining six data values on the EXTC card are the altered mass extinction coefficients for the six different wavelength bands, although only the 0.4- to 0.7- μm band requires the appropriate value, that is, the altered mass extinction coefficient times path length is equal to unity.

4. Results

The individual densities are printed in the following order, from least to most frequently changing variable: obscurant type, time step, horizontal (X), depth (Y), and height (Z). The order of the obscurant types in the density file is the same as the order they appear in phase I of the input. The depth values decrease from largest to smallest while the other three variables increase from smallest to largest value. This order was selected to be consistent with the Vis5D software. The size (bytes) of the aerosol cloud-density file is approximately nine times the product of the number of obscurants, time steps, and cells in the three orthogonal directions.

Figure 1 shows a visualization of the aerosol clouds of five different obscurant types with the use of the Vis5D software. Isosurfaces are shown for the aerosol clouds at 5 s after the starting time for each source. The five different aerosol clouds are the result of sources producing hexachloroethane smoke; fire smoke from a diesel, oil, and rubber mix; a white phosphorus (WP) munition; a red phosphorus munition; and an infrared grenade. The isosurface values for these sources are 10, 10, 10, 10, and 35 percent, respectively, of the maximum values. A degree of opacity is provided to the clouds in the foreground (yellow, green, and blue clouds) to reduce the likelihood that any clouds will be hidden. The volume drawn represents 40 m on a side with each cell being 2 m on a side; hence, there are 20 cells along each orthogonal direction.

The input file used to generate the aerosol clouds in figure 1 is given in appendix B-1. A number of data items in phase II in this file should be pointed out. The third FILE card contains the unit number 12.0 followed by the name of the density file. The fourth data value for the GREY card is 1.0, indicating that the optical depth option was selected. Finally, the last two values on the TPOS card indicate the length of the rectangular grid and the number of cells, respectively, in the Z -direction.

Appendix B-2 gives an abbreviated sample of the output. This abbreviated density file lists the header variables at the beginning of the file and three subheaders that precede the densities for each obscurant type. (The three subheader variables are shown for only the first two obscurant types in this appendix.) The density output file contains several variables required by Vis5D, including the number of obscurant types (line 7), the number of cells in the X -, Y -, and Z -directions (lines 14, 15, and 16, respectively), and the number of time steps (line 17). The Z -values (km), starting on line 19, are also shown in this abbreviated file. The size of this aerosol cloud-density file, which contained 200,000 density values ($20 \times 20 \times 20 \times 5 \times 5$), was approximately 1.8 MB.

The input values used to produce figure 2 are equivalent to those for figure 1 except that the cell size is increased to 4 m on a side. When comparing these two figures, one can see that the larger cell sizes for figure 2 result in a decreased resolution (reduced smoothness) of the clouds. While the isosurface values for figure 2 are the same percentages of the maximum values as those indicated for figure 1, the maximum density values for each respective cloud are different in the two figures.

In figure 3, two different sources (at different locations) that produced hexachloroethane resulted in aerosol clouds that overlapped 3 s after the start time for both sources. A program was written to check on the cloud-density file for this case and to compare it to the sums of the density files for the cases in which each source represented the only input. The results indicate that the values were added together correctly for those cells in which the two aerosol clouds overlapped with the use of this version of the COMBIC model. The input file for this example is shown in appendix B-3.

The multidimensional density grids output with the use of this version of COMBIC are not intended to represent the final product. These density files would then be used by AEROGEN in the WAVES software to represent man-made clouds to influence the WAVES radiative transfer results.

Figure 1. Vis5D
visualization of five
clouds, each of a
different obscurant
type.




Figure 2. Vis5D
visualization of five
clouds for case with
lower spatial resolution.





Figure 3. Vis5D
visualization of two
clouds of same
obscurant type.



5. Conclusions

This report provides documentation on the changes made to COMBIC to obtain a density output file for multiple obscurants in the scenario. It also indicates the caveats with which one should be familiar when developing the input for a particular simulation. The aerosol cloud-density output files from this version of COMBIC are expected to be quite useful as input to the AEROGEN software and eventual processing by WAVES. Once it is proven that these files can successfully be incorporated into WAVES, a future COMBIC implementation will optimize the data structures and access routines for obscurant density retrieval rather than use the current path integration method.

References

1. Alan Wetmore and Scarlett D. Ayres, *COMBIC, Combined Obscuration Model for Battlefield Induced Contaminants: Volume 1–Technical Documentation and Users Guide, Volume 2–Appendices*, U.S. Army Research Laboratory, ARL-TR-1831-1 and 2 (2000).
2. Patti Gillespie, Alan Wetmore, and David Ligon, *Weather and Atmospheric Effects for Simulation: Volume 1: WAVES98 Suite Overview*, U.S. Army Research Laboratory, ARL-TR-1721-1 (1998).
3. Vis5D is a system developed by Bill Hibbard, Johan Kellum, and Brian Paul under the University of Wisconsin Space Science and Engineering Center's Visualization Project. The system can be obtained from <http://www.ssec.wisc.edu/billh/vis5d.html>. The beta release of version 5.2 is available to beta testers at time of writing.

Appendix A. Header Variables

This appendix provides the list of header variables in the aerosol cloud-density file.

Header Variables in Density Output File

Characteristics of the data file
Contents of the data file
Experiment number
Date and time of experiment
Date and time experiment was executed
Number of defined grids (normally set equal to 1)
Number of obscurant types
Reference latitude
Reference longitude
Reference height
Grid identifier (first grid is numbered 0)
Longitude of the southwest corner point
Latitude of the southwest corner point
Number of cells in the X-direction
Number of cells in the Y-direction
Number of cells in the Z-direction
Number of time steps
Number of wavelengths (set equal to 1)
Height (km) of the center of each vertical level of the grid (the number of data values is equal to the number of cells in the Z-direction)
Wavenumbers (cm⁻¹) (the number of wavenumbers is equal to the number of wavelengths)

The following three header values precede each new obscurant type:
Description of data values in file
Obscurant type
Grid identifier number (set equal to 0)

Appendix B. Sample Inputs and Output

This appendix provides the input and abbreviated density-output files for selected cases discussed in the report.

B-1 Input File for Five Sources, Each of a Different Obscurant Type

```

WAVL      1.060000  0.000000  0.000000
COMBIC
PHAS      1.0      3.0      6.0      12.0      9.0      0.0      0.0
FILE      9.0history.out
NAME
Example 3 Sub A and Sub B
MET1      90.0      3.0      2.0      27.5      963.0      0.0      0.0
MUNT      3.000000  0.630000  1.000000  3.000000  92.000000  5.720000  1.000000
GO
MUNT      1.000000  0.790000  30.000000  14.000000  95.000000  7.850000  1.000000
BURN      300.000      0.0      0.0      0.0      0.0      1200.0      0.0008
GO
MUNT      2.000000  0.830000  8.000000  1.000000  82.000000  6.120000  1.000000
GO
MUNT      5.000000  0.850000  21.000000  5.000000  85.000000  6.500000  1.000000
GO
MUNT      7.000000  0.870000  32.000000  20.000000  87.000000  6.700000  1.000000
DONE
END
CONTINUE
WAVL      10.600000  0.000000  0.000000
COMBIC
PHAS      2.0      3.0      6.0      12.0      9.0      0.0      0.0
FILE      9.0history.out
FILE      12.0mulot1.out
NAME
Example 3
ORIG      0.000000  0.000000  0.000000  90.000000  270.000000  0.000000
LIST      1.000000  0.000000  5.000000  1.000000
SLOC      1.000000  3.000000  0.000000  300.000000  -3.000000  -12.000000  3.000000
SLOC      2.000000  1.000000  0.000000  300.000000  -7.000000  -6.000000  7.000000
SLOC      3.000000  2.000000  0.000000  300.000000  -15.000000  0.000000  2.000000
SLOC      4.000000  5.000000  0.000000  300.000000  4.000000  6.000000  4.000000
SLOC      5.000000  7.000000  0.000000  300.000000  -2.000000  12.000000  8.000000
OLOC      1.0      0.000      0.0      1.5      0.000      70.000
TLOC      1.0      0.000      0.0      0.5      1.0
EXTC      0.0      1.0      1.0      1.0      1.0      1.0      1.0
VIEW      1.0      1.0      40.0      40.0      20.0      20.0      90.0

```

GREY	9.0	.01	0.91	1.0	1.0	1.0	0.0
TPOS	0.0	0.0	0.0	0.0	0.0	40.0	20.0
DONE							
END							
STOP							

B-2 Abbreviated Density Output File for Five Sources, Each of a Different Obscurant Type

The relevant header variables are discussed in section 4 of the report.

densities from COMBIC

COMBIC to AEROGEN

1

200004211400

200004211500

1

5

-99.000

-99.000

-99.000

0

-78.000

39.000

20

20

20

5

1

0.00100

0.00300

0.00500

0.00700

0.00900

0.01100

0.01300

0.01500

0.01700

0.01900

0.02100

0.02300

0.02500

0.02700

0.02900

0.03100

0.03300

0.03500

0.03700

0.03900

18100

CLOUD DENSITIES: (g/m**3)

obs 3

0

0.0000

0.0000

0.0000

```

.
.
0.0000
0.0000
0.0000
0.0000
0.0594
0.1044
0.0971
0.0478
0.0124
0.0000
0.0000
0.0000
.
.
.
0.0000
0.0000
0.0000
CLOUD DENSITIES: (g/m**3)
obs 14
0
0.0000
0.0000
.
.
.
0.0000
0.0000
0.0000

```

B-3 Input File for Two Sources of the Same Obscurant Type

```

WAVL      1.060000  0.000000  0.000000
COMBIC
PHAS       1.0      3.0      6.0     12.0      9.0      0.0      0.0
FILE       9.0history.out
NAME
Example 3 Sub A and Sub B
MET1       90.0      3.0      2.0     27.5     963.0      0.0      0.0
MUNT       3.000000  0.630000  1.000000  3.000000  92.000000  5.720000  1.000000
DONE
END
CONTINUE
WAVL      10.600000  0.000000  0.000000
COMBIC
PHAS       2.0      3.0      6.0     12.0      9.0      0.0      0.0
FILE       9.0history.out
FILE      12.0mulot4.out
NAME
Example 3
ORIG       0.000000  0.000000  0.000000  90.000000  270.000000  0.000000
LIST       1.000000  0.000000  5.000000  1.000000
SLOC       1.000000  3.000000  0.000000  300.000000 -3.000000 -12.000000  3.000000
SLOC       1.000000  3.000000  0.000000  300.000000 -9.000000 -12.000000  3.000000
OLOC       1.0      0.000      0.0      1.5      0.000      70.000
TLOC       1.0      0.000      0.0      0.5      1.0
EXTC       3.0      1.0      1.0      1.0      1.0      1.0      1.0
VIEW       1.0      1.0      40.0     40.0     20.0     20.0     90.0
GREY       9.0      .01      0.91      1.0      1.0      1.0      0.0
TPOS       0.0      0.0      0.0      0.0      0.0      40.0     20.0
DONE
END
STOP

```

Distribution

Admnstr
Defns Techl Info Ctr
ATTN DTIC-OCF
8725 John J Kingman Rd Ste 0944
FT Belvoir VA 22060-6218

DARPA
ATTN S Welby
3701 N Fairfax Dr
Arlington VA 22203-1714

Defns Mapping Agcy
ATTN R Klotz
4211 Briars Rd
Olney MD 20832-1814

Defns Mapping Agcy
ATTN L-41 B Hagan
ATTN L-41 D Morgan
ATTN L-41 F Mueller
ATTN L-A1 B Tallman
3200 S 2nd Stret
ST Louis MO 63118

Mil Asst for Env Sci Ofc of the Undersec
of Defns for Rsrch & Engrg R&AT E LS
Pentagon Rm 3D129
Washington DC 20301-3080

Ofc of the Secy of Defns
ATTN ODDRE (R&AT)
The Pentagon
Washington DC 20301-3080

Ofc of the Secy of Defns
ATTN OUSD(A&T)/ODDR&E(R) R J Trew
3080 Defense Pentagon
Washington DC 20301-7100

AMC OMP/746 TS
ATTN A Chasko
PO Box 310
High Rolls NM 88325

AMCOM MRDEC
ATTN AMSMI-RD W C McCorkle
Redstone Arsenal AL 35898-5240

ARL Chemical Biology Nuc Effects Div
ATTN AMSRL-SL-CO
Aberdeen Proving Ground MD 21005-5423

Natl Ground Intllgnc Ctr
Army Foreign Sci Tech Ctr
ATTN CM
220 7th Stret NE
Charlottesville VA 22901-5396

US Army TRADOC
Battle Lab Integration & Techl Dirctr
ATTN ATCD-B
ATTN ATCD-B J A Klevecz
FT Monroe VA 23651-5850

CBIAC
ATTN J Rosser
PO Box 196 Gunpowder Br
Aberdeen Proving Ground MD 21010-0196

US Army Corps of Engrs
Engr Topographics Lab
ATTN CETEC-TR-G P F Krause
7701 Telegraph Rd
Alexandria VA 22315-3864

US Military Acdmy
Mathematical Sci Ctr of Excellence
ATTN MADN-MATH MAJ M Huber
Thayer Hall
West Point NY 10996-1786

Natl Security Agcy
ATTN W21 Longbothum
9800 Savage Rd
FT George G Meade MD 20755-6000

Dir for MANPRINT
Ofc of the Deputy Chief of Staff for Prsnl
ATTN J Hiller
The Pentagon Rm 2C733
Washington DC 20301-0300

Pac Mis Test Ctr Geophysics Div
ATTN Code 3250 Battalino
Point Mugu CA 93042-5000

Distribution (cont'd)

Redstone Scientific Info Ctr
ATTN AMSMI-RD-CS-R
Bldg 4484
Redstone Arsenal AL 35898

Sci & Technlgy
101 Research Dr
Hampton VA 23666-1340

SMC/CZA
2435 Vela Way Ste 1613
El Segundo CA 90245-5500

TECOM
ATTN AMSTE-CL
Aberdeen Proving Ground MD 21005-5057

US Army ARDEC
ATTN AMSTA-AR-TD
Bldg 1
Picatinny Arsenal NJ 07806-5000

US Army Avn & Mis Cmnd
ATTN AMSMI-RD-WS-PL G Lill Jr
Bldg 7804
Redstone Arsenal AL 35898-5000

US Army Combined Arms Combat
ATTN ATZL-CAW
FT Leavenworth KS 66027-5300

US Army CRREL
ATTN CRREL-GP F Scott
ATTN CRREL-GP J Koenig
ATTN CRREL-GP R Detsch
72 Lyme Rd
Hanover NH 03755-1290

US Army Dugway Proving Ground
ATTN STEDP 3
ATTN STEDP-MT-DA-L-3
ATTN STEDP-MT-M Bowers
Dugway UT 84022-5000

US Army Field Artillery Schl
ATTN ATSF-TSM-TA
FT Sill OK 73503-5000

US Army Infantry
ATTN ATSH-CD-CS-OR E Dutoit
FT Benning GA 30905-5090

US Army Info Sys Engrg Cmnd
ATTN AMSEL-IE-TD F Jenia
FT Huachuca AZ 85613-5300

US Army Materiel Sys Anal Actvty
ATTN AMXSU-CS Bradley
Aberdeen Proving Ground MD 21005-5071

US Army Natick RDEC Acting Techl Dir
ATTN SBCN-T P Brandler
Natick MA 01760-5002

US Army Natl Ground Intllgnc Ctr
ATTN IANG-TSC J Breeden
220 Seventh Stret NE
Charlottesville VA 22902

US Army OEC
ATTN CSTE-AEC-FSE
4501 Ford Ave Park Center IV
Alexandria VA 22302-1458

US Army Simulation Train & Instrmntn
Cmnd
ATTN AMSTI-CG M Macedonia
ATTN J Stahl
12350 Research Parkway
Orlando FL 32826-3726

US Army Spc Technlgy Rsrch Ofc
ATTN Brathwaite
5321 Riggs Rd
Gaithersburg MD 20882

US Army Tank-Automtv Cmnd RDEC
ATTN AMSTA-TR J Chapin
Warren MI 48397-5000

US Army Topo Engrg Ctr
ATTN CETEC-ZC
FT Belvoir VA 22060-5546

Distribution (cont'd)

US Army TRADOC
ATTN ATCD-FA
FT Monroe VA 23651-5170

US Army TRADOC Anal Cmnd—WSMR
ATTN ATRC-WSS-R
White Sands Missile Range NM 88002

US Army White Sands Missile Range
ATTN STEWS-IM-ITZ Techl Lib Br
White Sands Missile Range NM 88002-5501

Nav Air War Ctr Wpn Div
ATTN CMD 420000D C0245 A Shlanta
1 Admin Cir
China Lake CA 93555-6001

Nav Rsrch Lab
ATTN Code 4110 Ruhnke
Washington DC 20375-5000

Nav Rsrch Lab
ATTN Code 8150/SFA J Buisson
4555 Overlook Dr SW
Washington DC 20375-5354

Nav Surfc Warfare Ctr
ATTN Code B07 J Pennella 1470 Rm 1101
ATTN Code K12 E Swift
17320 Dahlgren Rd Bldg
Dahlgren VA 22448-5100

Nav Surfc Weapons Ctr
ATTN Code G63
Dahlgren VA 22448-5000

Ofc of Nav Rsrch
ATTN ONR 331 H Pilloff
800 N Quincy Stret
Arlington VA 22217

AFCCC/DOC
ATTN Glauber
151 Patton Ave Rm 120
Asheville NC 28801-5002

AFSPC/DRFN
ATTN CAPT R Koon
150 Vandenberg Stret Ste 1105
Peterson AFB CO 80914-45900

Air Force
ATTN Weather Techl Lib
151 Patton Ave Rm 120
Asheville NC 28801-5002

Air Force Rsrch Lab
ATTN IFOIL
26 Electronic Parkway
Rome NY 13441-4514

ASC OL/YUH
ATTN JDAM-PIP LT V Jolley
102 W D Ave
Eglin AFB FL 32542

DOT AFSPC/DRFN
ATTN H Skalski
150 Vandenberg Stret
Peterson AFB CO 80914

Holloman AFB
ATTN K Wernie
1644 Vandergrift Rd
Holloman AFB NM 88330-7850

Phillips Lab
ATTN PL/LYP
Hanscom AFB MA 01731-5000

Phillips Lab Atmos Sci Div
Geophysics Dirctr
ATTN PL-LYP Chisholm
ATTN PL/LYP 3
Kirtland AFB NM 87118-6008

TAC/DOWP
Langley AFB VA 23665-5524

US Air Force Rsrch Lab
ATTN Battlespace Environment Division
ATTN USBL P Tattelman
29 Randolph Rd
Hanscom AFB MA 01731

USAF Rome Lab Tech
ATTN Corridor W Ste 262 RL SUL
26 Electr Pkwy Bldg 106
Griffiss AFB NY 13441-4514

Distribution (cont'd)

Los Alamos Natl Lab
ATTN M Mosier
PO Box 1663 Mail Stop P364
Los Alamos NM 87545

NASA Marshal Spc Flt Ctr
Atmos Sci Div
ATTN Code ED 41 1
Huntsville AL 35812

NIST
ATTN MS 847.5 M Weiss
325 Broadway
Boulder CO 80303

SpceEnvironLab/NOAA
ATTN R/E/SE J Kunches
325 Broadway
Boulder CO 80303

Stanford Univ
ATTN HEPL/GP-B D Lawrence
ATTN HEPL/GP-B T Walter
Stanford CA 94305-4085

Univ of Texas
Appld Rsrch Lab
ATTN B Renfro
ATTN J Saunders
ATTN R Mach
PO Box 8029
Austin TX 78713-8029

Aerospace
ATTN J Langer
PO Box 92957 M4/954
Los Angeles CA 90009

Aerospace
ATTN M Dickerson
PO Box 92957
Los Angeles CA 90009-2957

ARINC
ATTN P Mendoza
4055 Hancock Stret
San Diego CA 92110

BD Systems
ATTN J Butts
385 Van Ness Ave #200
Torrance CA 90501

Dept of Commerce Ctr
Mountain Administration
ATTN Spprt Ctr Library R51
325 S Broadway
Boulder CO 80303

Hewlett-Packard Co
ATTN J Kusters
5301 Stevens Creed Blvd
Santa Clara CA 95052

Hicks & Assoc Inc
ATTN G Singley III
1710 Goodrich Dr Ste 1300
McLean VA 22102

ITT Aerospace
ATTN MS 2511 R Peller
ATTN MS 8528 H Rawicz
ATTN MS 8538 L Doyle
100 Kingsland Rd
Clifton NJ 07014

KERNCO
ATTN R Kern
28 Harbor Stret
Danvers MA 01923

Lockheed Martin
ATTN B Marquis
1250 Academy Park Loop #101
Colorado Springs CO 80912

LORAL
ATTN B Mathon
700 N Frederick Pike
Gaithersburg MD 20879

LORAL Fed Sys
ATTN J Kane
ATTN M Baker
9970 Federal Dr
Colorado Springs CO 80921

Distribution (cont'd)

Natl Ctr for Atmos Rsrch
ATTN NCAR Library Serials
PO Box 3000
Boulder CO 80307-3000

NCSU
ATTN J Davis
PO Box 8208
Raleigh NC 27650-8208

Ontar Corp
9 Village Way
North Andover MA 01845-2000

Overlook Sys
ATTN D Brown
ATTN T Ocvirk
1150 Academy Park Loop Ste 114
Colorado Springs CO 80910

Pacific Mis Test Ctr Geophysics Div
ATTN Code 3250
Point Mugu CA 93042-5000

PAQ Commctn
ATTN Q Hua
607 Shetland Ct
Milpitas CA 95035

Rockwell CACD
ATTN L Burns
400 Collins Rd NE
Cedar Rapids IA 52398

Rockwell Collins
ATTN C Masko
400 Collins Rd NE
Cedar Rapids IA 52498

Rockwell DA85
ATTN W Emmer
12214 Lakewood Blvd
Downey CA 92104

Rockwell Spc Ops Co
ATTN AFMC SSSG DET2/NOSO/Rockwell
R Smetek
ATTN B Carlson
442 Discoverer Ave Ste 38
Falcon AFB CO 80912-4438

Rockwell Spc Sys Div
ATTN Mailcode 841-DA49 D McMurray
12214 Lakewood Blvd
Downey CA 90241

Trimble Nav
ATTN P Turney
585 N Mary
Sunnyvale CA 94086

Director
US Army Rsrch Lab
ATTN AMSRL-RO-D JCI Chang
ATTN AMSRL-RO-EN W D Bach
PO Box 12211
Research Triangle Park NC 27709

US Army Rsrch Lab
ATTN AMSRL-CI-EA J Cogan
ATTN AMSRL-CI-EW D Hooch
ATTN AMSRL-SL-EM R Sutherland
ATTN AMSRL-SL-EM S Ayres
ATTN AMSRL-BE B Sauter
ATTN AMSRL-BE D Knapp
White Sands Missile Range NM 88002-5501

US Army Rsrch Lab
ATTN AMSRL-D D R Smith
ATTN AMSRL-DD J M Miller
ATTN AMSRL-CI-AI-R Mail & Records
Mgmt
ATTN AMSRL-CI-AP Techl Pub (2 copies)
ATTN AMSRL-CI-LL Techl Lib (2 copies)
ATTN AMSRL-CI-EM D Garvey
ATTN AMSRL-CI-EP A Wetmore
(10 copies)
ATTN AMSRL-CI-EP M Mungiole (5 copies)
Adelphi MD 20783-1197

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.				
1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE March 2001		3. REPORT TYPE AND DATES COVERED Final, Jan to Oct 2000
4. TITLE AND SUBTITLE COMBIC Modifications to Determine Aerosol Cloud Densities for Multiple Obscurant Input Sources			5. FUNDING NUMBERS DA PR: AH71 PE: 622784H71	
6. AUTHOR(S) Michael Mungiole and Alan Wetmore				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army Research Laboratory Attn: AMSRL-CI-EP email: mmungiole@arl.army.mil 2800 Powder Mill Road Adelphi, MD 20783-1197			8. PERFORMING ORGANIZATION REPORT NUMBER ARL-TR-865	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army Research Laboratory 2800 Powder Mill Road Adelphi, MD 20783-1197			10. SPONSORING/MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES ARL PR: 1FEH36 AMS code: 622784H7111				
12a. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited.			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) Modifications were made to the Combined Obscuration Model for Battlefield Induced Contaminants (COMBIC) code to obtain aerosol cloud-density values for multiple obscurant types. The main purpose of COMBIC has traditionally been to obtain the transmittance or optical depth for one or more lines of sight (LOSs). If one specifies optical depth, uses consistent units, and ensures that the product of mass extinction coefficient and optical path length is unity, output values will be numerically equal to the cloud density (g/m^3). This report provides information on the required input values, the modifications made to COMBIC, and the resulting output obtained when one or more sources comprising various obscurant types are provided as input. Examples are included that show various cases containing sources with one or more obscurant types as input. The density output files and the resulting visualized clouds are also given in this report. Specific recommendations for the appropriate input values required to produce valid cloud-density grids are indicated.				
14. SUBJECT TERMS Multiple obscurants, cloud concentrations, densities			15. NUMBER OF PAGES 28	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT Unclassified	20. LIMITATION OF ABSTRACT UL	